

## MAGNIFIERS WITH ILLUMINATION

- Glass lens
- Powered by 3xAAA batteries (included)



(mm)


Code	Magnification	Lens diameter (ØD)	L	h
7513-2	2X	Ø75mm	170	90
7513-4	4X	Ø50mm	145	90



7513-2




7513-4



## THREE WAYS MAGNIFIER WITH ILLUMINATION


- Plastic lens
- Powered by 2xAA batteries (included) or power adapter (110~240V, 50~60Hz)



three-way use



Code	Magnification	Lens diameter (ØD)	Lens diameter (Ød)
7512-1	2X/4X	Ø120mm	Ø28mm



Unit: mm




7512-1



## MOTORIZED 360° SWIVEL VIDEOSCOPIES

IP65  
WATERPROOF

ATTENTION: THE CABLE CAN BE BENT BUT CAN'T BE SET AT A FIXED SHAPE

TUNGSTEN WIRE WEAVED CABLE  
RESISTANCE TO BREAK AND WEAR


bend in any direction


360° swivel in clockwise  
and counter-clockwise


bend within ±120°



- Motorized joystick to bend the probe at any direction

### SPECIFICATION

Code	ISV-4000D	ISV-4001D	ISV-5000D	ISV-5001D
Lens	diameter (D)	6mm	4.5mm	
	focus distance (F)	15mm~∞	8~80mm	
	illumination	6pcs LED	6pcs LED	
	pixel	0.41M		
	resolution	720x576		
	dust/waterproof	IP65		
	bend control	motorized joystick		
Cable	length	1.5m	3m	1.5m
	type	tungsten wire weaved cable		
Main unit	function	take picture, take video		
	file format	picture: JPG, video: AVI		
	image process	brightness, image quality zoom (1X, 2X, 3X)		
	memory	8G SD card		
	output	TV, USB		
Weight	power supply	rechargeable battery (for 4 hours working) AC/DC adapter (for continuous working)		



ISV-4000D



lens with LED  
adjustable illumination

tungsten wire weaved  
cable length: 1.5m


lens with  
adjustable  
LED illumination

### STANDARD DELIVERY

Main unit	1pc
Cable with lens	1pc
8G SD card	1pc
AC/DC adapter	1pc
Video output cable	1pc
USB cable	1pc



focus distance




angle of view: 110°

ATTENTION: THE CABLE CAN BE BENT BUT CAN'T BE SET AT A FIXED SHAPE

STEEL WIRE WEAVED CABLE  
RESISTANCE TO BREAK AND WEAR

IP65  
WATERPROOF

## MANUAL 360° SWIVEL VIDEOSCOPIES



base (optional)

### STANDARD DELIVERY

Main unit	1pc
Cable with lens	1pc
8G SD card	1pc
AC/DC adapter	1pc
Video output cable	1pc
USB cable	1pc

### OPTIONAL ACCESSORY


Base	ISV-2000D-BASE
------	----------------



ISV-2000D

### SPECIFICATION

Code		ISV-2002D	ISV-2000D	ISV-2001D	ISV-3002D	ISV-3000D	ISV-3001D
Lens	diameter (D)	6.5mm			4.5mm		
	focus distance (F)	15mm~∞			8~80mm		
	illumination	8pcs LED			6pcs LED		
	pixel	0.3M					
	resolution	640x480					
	dust/waterproof	IP65					
	bend control	manual joystick					
Cable	length	1m	1.5m	3m	1m	1.5m	3m
	type	steel wire weaved cable					
Main unit	function	take picture, take video					
	file format	picture: JPG, video: AVI					
	image process	brightness, image quality zoom (1X, 2X, 3X, 4X, 5X)					
	memory	8G SD card					
	output	TV, USB					
	power supply	rechargeable battery (for 2 hours working) AC/DC adapter (for continuous working)					
Weight		600g	650g	800g	550g	600g	700g



output image to TV  
(maximum size 12")



### SPECIFICATION

Diameter (D)	5.5mm
Length (L)	350mm
Dust/waterproof probe	IP57
Pixel	0.3M
Resolution	640x480
Frame rate	30fps
Function	take picture, take video
File format	picture: JPG, video: AVI
Memory	2G SD card
Output	TV, USB
Power supply	rechargeable battery (for 3 hours working)
Weight	570g



IP57  
WATERPROOF


## SIDE VIEW VIDEOSCOPE (RIGID) CODE ISV-RV



to observe internal wall of holes  
(minimum diameter Ø10mm)

### STANDARD DELIVERY

Main unit	1pc
2G SD card	1pc
AC/DC adapter	1pc
Video output cable	1pc
USB cable	1pc



ATTENTION: THE CABLE CAN BE BENT  
BUT CAN'T BE SET AT A FIXED SHAPE

STEEL WIRE WEADED CABLE  
RESISTANCE TO BREAK AND WEAR

OPTIONAL CABLE  
LENGTH 3M, 5M AND 10M


IP65  
WATERPROOF



## VIDEOSCOPE CODE ISV-E10


### SPECIFICATION

Lens	diameter	5.5mm
	pixel	0.3M
	resolution	640×480
	frame rate	30fps
Cable	length	1m
	type	steel wire weaved cable
Main unit	function	take picture, take video
	file format	picture: JPG, video: AVI
	image process	brightness, contrast, color saturation
	memory	2G SD card
	output	TV, USB
Weight	power supply	rechargeable battery (for 3 hours working)
		450g




### STANDARD DELIVERY

Main unit	1pc
Cable with lens	1pc
2G SD card	1pc
45° mirror	1pc
AC/DC adapter	1pc
Video output cable	1pc
USB cable	1pc
Lens cleaning kit	1pc




### OPTIONAL ACCESSORY

35° mirror	ISV-E55-M35
60° mirror	ISV-E55-M60




IP57  
WATERPROOF

the cable has high illumination  
and can be set at any shape.  
it is suitable to observe large  
internal space like turbocharger.



lens with 8pcs LED  
adjustable illumination



memory cable  
length: 1m



### SPECIFICATION

Lens	diameter (D)	12mm
	pixel	0.4M
	resolution	720×682
	frame rate	30fps
Cable	length	1m
	type	memory (can be set at any shape)
Main unit	function	take picture, take video
	file format	picture: JPG, video: AVI
	image process	brightness, contrast, color saturation
	memory	2G SD card
	output	TV, USB
Weight	power supply	rechargeable battery (for 3 hours working)
		600g


### STANDARD DELIVERY

Main unit	1pc
Cable with lens	1pc
2G SD card	1pc
AC/DC adapter	1pc
Video output cable	1pc
USB cable	1pc
Lens cleaning kit	1pc

### OPTIONAL ACCESSORY

45° mirror	ISV-E20-MIRROR
Hook	ISV-E20-HOOK
Magnet pick up	ISV-E20-MAGNET

## VIDEOSCOPE CODE ISV-E20





## PIPE VIDEOSCOPE CODE ISV-VP280

### SPECIFICATION

Lens	diameter	28mm
	dust/waterproof	IP68
	pixel	0.3M
	resolution	640×480
Cable	frame	30fps
	length	22m
	dust/waterproof	IP68
	type	semi-rigid
Main unit	function	take picture and video
	file format	picture: JPG, video: ASF
	image process	mirror, rotate, zoom (1.5X, 2X)
	memory	4G SD card
	output	TV, USB
power supply		4×AA batteries
Weight		5kg


### STANDARD DELIVERY

Main unit	1pc
Cable with lens	1pc
Stand	1pc
4G SD card	1pc
Ø100mm brush	1pc
AA battery	4pcs
AAA battery	2pcs
Video output cable	1pc
USB cable	1pc



ATTENTION: RESISTANCE TO ACID AND ALKALI LIQUID (CONSULT IS NEEDED)

**IP68**  
WATERPROOF



### OPTIONAL ACCESSORY


Ø50mm centering ring	ISV-VP280-R50
Ø150mm brush	ISV-VP280-B150

## RIGID BORESCOPES

- Focus distance: 2mm, depth of view: 5~100mm
- Dust/waterproof level: IP67
- Can be used in the liquid with temperature -10°C~85°C



ISV-1H4300



### SPECIFICATION

Code	Length (L)	View direction (α)	Diameter (D)	Angle of view (θ)
ISV-1H4170	174mm	0°	4mm	≥60°
ISV-1H4173	174mm	30°		
ISV-1H4177	174mm	70°		
ISV-1H4179	166mm	90°		
ISV-1H4300	302mm	0°		
ISV-1H4303	302mm	30°		
ISV-1H4307	302mm	70°		
ISV-1H4309	297mm	90°		

Code	Length (L)	View direction (α)	Diameter (D)	Angle of view (θ)
ISV-1H6200	209mm	0°	6mm	≥70°
ISV-1H6203	209mm	30°		
ISV-1H6207	209mm	70°		
ISV-1H6209	166mm	90°		
ISV-1H6320	328mm	0°		
ISV-1H6323	328mm	30°		
ISV-1H6327	328mm	70°		
ISV-1H6329	330mm	90°		

### OPTIONAL ACCESSORY

LED light handle	ISV-1HLED
Adjustable LED light source	ISV-1LED1
Camera	ISV-1CAM



LED light handle (optional)



adjustable LED light source (optional)



camera (optional)

LED LIGHT HANDLE  
CODE ISV-1HLED

battery (included)



charger (included)



- For rigid borescopes (code ISV-1Hxx)



## SPECIFICATION

Power	3W
Battery	3.7V rechargeable battery (for 2 hours working)
Dimension	120×27×27mm
Weight	300g

## STANDARD DELIVERY

Main unit	1pc
Battery	1pc
Charger	1pc

ADJUSTABLE LED LIGHT SOURCE  
CODE ISV-1LED1

- For rigid borescopes (code ISV-1Hxx)
- High LED illumination and brightness is adjustable
- For long time work with low noise



## SPECIFICATION


Color temperature	5600K
Cooling	fan cooling
Power	AC110~220V, 50/60Hz
Dimension	400×300×112mm
Weight	7kg

## STANDARD DELIVERY

Main unit	1pc
1.8m optical fiber cable	1pc

software CD  
(included)

- For rigid borescopes (code ISV-1Hxx)
- Connected to computer USB port
- Auto-exposure, auto-gain, auto white balance
- Focus is adjustable

CAMERA  
CODE ISV-1CAM

## SPECIFICATION

Sensor	color CMOS
Pixel	1.3M
Resolution	1280×1024
Frame rate	15~50fps
Software	take picture, take video, zoom in, zoom out, image rotation
Power supply	USB

## STANDARD DELIVERY

Camera	1pc
Connector	1pc
USB cable and software	1pc

