


Ref. **3100**

MACHO RECTO MÁQUINA MÉTRICA MANGO REFORZADO


Reinforced Shank Metric Machine Straight Tap

Taraud droit machine métrique queue renforcée



HSSE 5%Co	DIN 371	B 3,5-5h	GUN	Tol. 6H	α 10-12°	60°
--------------	------------	-------------	-----	------------	--------------------	-----

Material		Vc (m/min)
Grupo	Sub.	5% Co
P	P.1	6-10
N	N.1	5-8
	N.3	15-35
	N.4	14-20



Avance $f = P$ (Paso - Pitch - Pas)

V_f (mm/min.) = r.p.m. x f

r.p.m. = $\frac{V_c \times 1.000}{\pi \times \phi}$

M	P	L mm	l mm	d mm	a mm	Z	N° Art. 5% Co	€
M2	0,40	45	9	2,80	2,10	3	62771	16,31
M2,5	0,45	50	9	2,80	2,10	3	76724	16,31
M2,6	0,45	50	9	2,80	2,10	3	76725	16,31
M3	0,50	56	11	3,50	2,70	3	62774	9,25
M3,5	0,60	56	13	4,00	3,00	3	62777	14,66
M4	0,70	63	13	4,50	3,40	3	62780	9,78
M4,5	0,75	70	16	6,00	4,90	3	76728	22,20
M5	0,80	70	16	6,00	4,90	3	62783	9,78
M6	1,00	80	19	6,00	4,90	3	62789	10,75
M7	1,00	80	19	7,00	5,50	3	76733	17,00
M8	1,25	90	22	8,00	6,20	3	62795	12,02
M9	1,25	90	18	9,00	7,00	3	62798	20,08
M10	1,50	100	24	10,00	8,00	3	62807	14,80



New! PASTA DE CORTE - Cutting Paste - Pâte de coupe

Pasta con propiedades lubricantes extremas. La pasta se asienta en las aristas de corte y se licua durante la operación de corte.

Ideal para todas las operaciones como roscado, taladrado y fresado de materiales difíciles de cortar como acero inoxidable, acero Cr-Ni, titanio, acero al manganeso, etc.

Paste with extreme lubricating properties. The paste settles on the cutting edges and liquefies during the cutting operation.

Ideal for all operations such as the threading, drilling and milling of difficult-to-cut materials such as stainless steel, Cr-Ni steel, titanium, manganese steel, etc.

Pâte aux propriétés lubrifiantes extrêmes. La pâte se dépose sur les bords de coupe et se liquéfie pendant l'opération de coupe.

Idéale pour toutes les opérations telles que le taraudage, le perçage et le fraisage de matériaux difficiles à couper comme l'acier inoxydable, l'acier Cr-Ni, le titane, l'acier au manganèse, etc.



Cont. 250ml
N° Art. 53954
€ 15,75



Cont. 750ml
N° Art. 53956
€ 26,24



Sumerja la herramienta de corte en la pasta para obtener resultados optimizados

Dip the cutting tool into the paste for optimised results

Trempez l'outil de coupe dans la pâte pour des résultats optimisés

Gama completa en la pagina 555

Complete range on page 555

Gamme complète à la page 555